

NOVINKA
Dostupné od léta 2017



Objednací číslo

OTL 120

OTL 150

OTL 240

OTL 300

Šedá	●	MAA1120A10	MAA1150A10	MAA1240A10	MAA1300A10
Modrá	●	MAA1120B10	MAA1150B10	MAA1240B10	MAA1300B10
Žluto-zelená	●	MAA1120Y10	MAA1150Y10	MAA1240Y10	MAA1300Y10

Technická data

Rozsah upínaných vodičů Cu, Al [mm ²]	16 ÷ 120	25 ÷ 150	35 ÷ 240	95 ÷ 300
Jmenovité napětí [V]	1000	1000	1000	1000
Jmenovitý proud [A]	280 (Cu) / 250 (Al)	320 (Cu) / 290 (Al)	425 (Cu) / 380 (Al)	490 (Cu) / 440 (Al)
Šířka / výška / délka [mm]	30 / 53 / 84	31 / 54 / 84	37 / 65 / 106	37 / 65 / 106
Hlava šroubu	inbus č. 6	inbus č. 6	inbus č. 8	inbus č. 8
Utahovací moment [Nm]	12 Nm (16 ÷ 35 mm ²) 25 Nm (50 ÷ 120 mm ²)	14 Nm (25 ÷ 50 mm ²) 30 Nm (70 ÷ 150 mm ²)	26 Nm (35 ÷ 120 mm ²) 40 Nm (150 ÷ 240 mm ²)	30 Nm (95 ÷ 150 mm ²) 45 Nm (185 ÷ 300 mm ²)
Způsob uchycení	lišta DIN, šrouby	lišta DIN, šrouby	lišta DIN, šrouby	lišta DIN, šrouby
Hmotnost [g]	85	100	195	212
Balení [ks]	● 30 / ● 15	● 20 / ● 10	● 10 / ● 3	3

Rozměry

