

Tabulka připojitelnosti vodičů svorek OTL



Typ	Průřez vodiče [mm2] / počet vodičů (Al / Cu)																Jmenovitý utahovací moment	In [A]
	1.5	2.5	4	6	10	16	25	35	50	70	95	120	150	185	240	300	[Nm]	Al / Cu
OTL 16	1 / 3	1 / 3	1 / 2	1 / 2	1 / 1	1 / 1											1.5 Nm (1.5 - 6 mm2) 7 Nm (10 - 16 mm2)	75 / 82
OTL 35																	3 Nm (2.5 - 16 mm2) 6 Nm (25 - 35 mm2)	120 / 135
OTL 35-2		1 / 3	1 / 3	1 / 3	1 / 3	1 / 2	1 / 1	1 / 1										
OTL 35-3X																		
OTL 35-5X																		
OTL 50																	1.5 Nm (1.5 - 2.5 mm2) 5 Nm (4 - 10 mm2) 10 Nm (16 - 50 mm2)	145 / 160
OTL 50-2	1 / 3	1 / 3	1 / 3	1 / 3	1 / 3	1 / 3	1 / 2	1 / 1										
OTL 50-3																		
OTL 95																	12 Nm (6 - 25 mm2) 22Nm (35 - 95 mm2)	220 / 245
OTL 95-2				1 / 3	1 / 3	1 / 3	1 / 3	1 / 2	1 / 1	1 / 1	1 / 1							
OTL 95-3																		
OTL 120																	12 Nm (16 - 35 mm2) 25 Nm (50 - 120 mm2)	250 / 280
OTL 120-2						1 / 3	1 / 3	1 / 3	1 / 2	1 / 1	1 / 1	1 / 1						
OTL 150																	14 Nm (25 - 50 mm2) 30 Nm (70 - 150 mm2)	290 / 320
OTL 150-2							1 / 3	1 / 3	1 / 3	1 / 2	1 / 1	1 / 1	1 / 1					
OTL 150-3																		
OTL 240																	26 Nm (35 - 120 mm2) 40 Nm (150 - 240 mm2)	380 / 425
OTL 240-2								1 / 3	1 / 3	1 / 3	1 / 2	1 / 2	1 / 1	1 / 1	1 / 1			
OTL 300																	30 Nm (95 - 150 mm2) 45 Nm (185 - 300 mm2)	440 / 490
OTL 300-2											1 / 3	1 / 2	1 / 2	1 / 1	1 / 1	1 / 1		