


**NOVINKA**  
Dostupné od léta 2017


**Objednávací číslo**
**OTL 150-2**
**OTL 240-2**
**OTL 300-2**

Šedá	●	MAA2150A10	MAA2240A10	MAA2300A10
Modrá	●	MAA2150B10	MAA2240B10	MAA2300B10
Žluto-zelená	●	MAA2150Y10	MAA2240Y10	MAA2300Y10

**Technická data**

Rozsah upínaných vodičů Cu, Al [mm <sup>2</sup> ]	25 ÷ 150	35 ÷ 240	95 ÷ 300
Jmenovité napětí [V]	1000	1000	1000
Jmenovitý proud [A]	320 (Cu) / 290 (Al)	425 (Cu) / 380 (Al)	490 (Cu) / 440 (Al)
Šířka / výška / délka [mm]	51 / 54 / 84	60 / 65 / 106	68 / 65 / 106
Hlava šroubu	inbus č. 6	inbus č. 8	inbus č. 8
Utahovací moment [Nm]	14 Nm (25 ÷ 50 mm <sup>2</sup> ) 30 Nm (70 ÷ 150 mm <sup>2</sup> ) -	26 Nm (35 ÷ 120 mm <sup>2</sup> ) 40 Nm (150 ÷ 240 mm <sup>2</sup> ) -	30 Nm (95 ÷ 150 mm <sup>2</sup> ) 45 Nm (185 ÷ 300 mm <sup>2</sup> )
Způsob uchycení	lišta DIN, šrouby	lišta DIN, šrouby	lišta DIN, šrouby
Hmotnost [g]	170	340	399
Balení [ks]	● 10 / ● 5	● 6 / ● 3	6

## Rozměry

